


■ 系列
此型號是屬於長久生命週期的產品系列。



规格

传感器	
传感器技术	CMOS 黑白
快门	全局快门
特征	线性
像素级别	1.6 MP
分辨率	1.58 百万像素
分辨率 (水平 x 垂直)	1456 x 1088 像素
长宽比	4:3
模数转换器	12 bit
色深 (相机)	12 bit
光学传感器等级	1/2.9"
光学尺寸	4.996 mm x 3.747 mm
光学传感器对角线	6.25 mm 1/2.9"
像素尺寸	3.45 µm
CRA (雷·安格尔局长)	0 °
生产商	Sony
传感器型号	IMX273LLR-C
增益 (主色/RGB)	25.4x/-
水平方向上的AOI	相同的帧率
垂直方向上的AOI	增加的帧率
AOI图像宽度, 步长	256 / 2
AOI图像高度, 步长	1 / 1
AOI位置网格 (水平方向/垂直方向)	2 / 1
水平方向上的像素融合	增加的帧率
垂直方向上的像素融合	增加的帧率
像素融合方法	水平: 附加 / 垂直: 附加
像素融合因子	2x2
水平方向上的 decimation (子抽点)	增加的帧率
垂直方向上的 decimation (子抽点)	增加的帧率
Decimation (子抽点)方法	M/C自动



可能随技术进步有所更改 (2026-09-12)

型号

自由运行模式下帧率	79 fps
帧率触击(持续的)	79 fps
帧率触击(最大值)	82 fps
曝光时间 (最小值 - 最大值)	0.025 ms - 2000 ms
长时间曝光 (最长)	90000 ms
线速自由运行模式 (线阵扫描)	2045 1/s
线速触发模式 (线阵扫描)	2191 1/s
每帧行数 (线阵扫描)	8000
功耗	1.4 W - 3.1 W
图像内存	128 MB

HDR

模式	Sequencer
----	-----------

工作环境要求

下列温度值指相机外部温度。

运行期间允许的装置温度范围	0 °C - 55 °C / 32 °F - 131 °F
储存期间允许的环境温度	-20 °C - 60 °C / -4 °F - 140 °F
湿度 (相对湿度 , 无凝结)	20 % - 80 %

连接器

接口连接器	GigE RJ45 , 螺丝锁紧式
I/O连接器	Hirose 8-pin连接器 (HR25-7TR-8PA (73))
电源	12 V - 24 V或PoE

引脚分配 I/O 连接器

1	接地 (GND)
2	带光耦闪光输出 (-) - Line 1
3	GPIO接口 1 - Line 2
4	带光耦触发输入 (-) - Line 0
5	带光耦闪光输出 (+) - Line 1
6	GPIO接口 2 - Line 3
7	带光耦触发输入 (+) - Line 0
8	输入电源 (VCC) 12-24 V DC



外观设计

镜头接口	C接口
防护等级	IP30
尺寸 高/宽/长	29.0 mm x 29.0 mm x 29.0 mm
总重量	51 g
外壳材料	镁 / 不锈钢

Features

相机图像预处理功能列表。

工作台的所有功能均可通过我们的 ids peak 软件在主机上进行图像预处理 (取决于传感器型号) 。

可能随技术进步有所更改 (2026-09-12)

GV-5040CP-M-GL Rev.2.2 (AB12612)

图像采集

Freerun	✓
Software trigger	✓
Hardware trigger	✓
Trigger controlled exposure	✓
Denoiser	✓
Long exposure	✓
Line scan	✓

闪烁

Flashing	✓
PWM flashing	✓

图像调整

Auto exposure	✓
Auto gain	✓
Auto whitebalance	-
Color correction	-
Gamma	✓
LUT	✓
Mirror/flip	X/Y

车载图像处理

Pixel formats	Mono8 Mono10 Mono10p Mono12 Mono12p
Region of interest	✓
Decimation (FPGA)	✓
Decimation (Sensor)	2x2
Binning (FPGA)	✓
Binning (Sensor)	2x2 Increases frame rate.

其他

IP settings	✓
Bandwidth management	✓
Chunks	✓
Sequencer	✓
PTP	✓
Firmware update	✓
1st supported firmware version	2.10